TECHNICAL SPECS - LIGHT	
Lights network	Subnet mask: 255.255.0.0
	IP-Range Desk: 10.101.11.0
FOH	To stage left 2x ethercon RJ45 cat 6a
	To stage right 2x ethercon RJ45 cat 6a
	ELC dmxLAN node 3 If necessary lightnetwork is available through DMX.
Flybars	ELC dmxLAN Node 8 Flybars:
	House + Dimmers = SACN 1
	Flybar 2 = SACN 3
	Flybar 4 = SACN 4 Flybar 6 = SACN 5
	Flybar 8 = SACN 6
	Flybar 10 = SACN 7
	Front T1 = SACN 8
Stage Left and Right	From FOH left and right 2x ethercon RJ45 cat 6a
3 3 .	ELC dmxLAN node 3 Stage left and right
Dimming	Our flybars have dimmers on request.
· ·	On stage we can provide 1x SRS 24 dimmer channels – 2.3 kW each
	Every flybar has two fixed voltage circuits at 240 volt max 2.3 kW each
Desk	1x Avolite Arena
	Console IP: 10.101.11.21
Titan version	When needed please contact us for our firmware version.
Orchestra fixtures	Above the stage are 36 x ETC D60 studio HD HSIC (7DMX) spots, the D60 are fixed in
sACN 34	our stage ceiling and are not moveable.
Fixed Moving led	We can provide a Fixed Robe light set:
Fixtures	• 10x Robe T1 Profile
	• 6x Robe Spider
	• 20x Robe 150 Led Beam Fixtures position are fixed on Lx.
	If you want to use a Lx in other flybars than please contact our production team.
Front fixtures	14x Niethammer HPZ211 profile 2 kW – 10 / 22°
sACN 33	8x Niethammer HPZ215 profile 2 kW – 15 / 40°
	1x Robert Juliat Aramis followspot 2,5 kW
	6x Robe T1 profile
Horizon lights	On request! 12 x Robert Juliat LEDhorizon Dalis 860 M2
Other fixtures	On request we can provide conventional fixtures.
	If needed please contact our production team.
Smoke	2x Swefog Ultimate 3000 + 2x DMX Fan
DWG	Contact us for our DWG.
Guest Desk IP	10.101.11.11 subnetmask 255.255.0.0

DOWNLOADS

FULL LIGHT SET-UP >

FULL LIGHT SET-UP FRONT >



